

Fireshield® Bolt Caps

Fire rated bolt caps for use with the Fireshield range of intumescent coating systems.

Fireshield® Bolt Caps are a simple to use solution to fire rate all bolt and nut connections up to 90 minutes FRR. Use on interior and exterior structural steel sections for C1 to C5 Very High exterior environments.

Characteristics:

- Intumescent fire rated technology.
- Simple installation using 3.5kg 920KS.
- Certified and tested to 90 minutes FRR.
- M12 to M36 available in bolt or nut configurations.
- Galvanised bolts should be primed first.

Advantages:

- Consistent quality and simple inspection/QA.
- Quick installation on site.
- 20-40% approximate saving over conventional fire rating method.

At A Glance

| | |
|--------------------|----------------------------|
| Type | Fire rated bolt caps |
| Fire Protection | Up to 90 minutes FRR |
| Bolt and Nut Sizes | M12 to M36 |
| Adhesive | Fireshield 920KS 3.5kg kit |
| VOC | Zero |
| Install Location | C1 - C5 Very High Exterior |



P 0800 347 374
 P 1-800 092 097
 E info@fireshieldcoatings.com
www.fireshieldcoatings.com

Issued 12th April 2023
 PIS No PIS-FSBCAP-NZAU-01

